



# ULTIMATE MP COMPETITIVE COMPARISON GUIDE

Titebond® WeatherMaster™ ULTIMATE MP offers unbeatable adhesion to aluminum, painted metal, PVC, concrete, wood, masonry, vinyl, glass, plastic, steel and most common building materials such as wall panels, siding, flashing, and sheet metal including Kynar™ coated metal panels. It adheres well to damp surfaces and provides a weather-tight seal against water, wind, dust and dirt.

Ultimate performance. Ultimate results. ULTIMATE MP.

## Ready to Use

No mixing or primer required;  
reduces labor and installation cost

## Ultra Low VOC

VOC-compliant in all 50 states

## Joint Movement Capability ± 50%

Remains permanently flexible

## Weather Resistant

Produces long-lasting weather-tight seals

## Paintable

May be painted with water-based paints  
1 hour after application\*

## Wide Temperature Application Range

Suitable for all climates

## Ideal Applications Include:

- General roofing applications
- Gutters
- Metal and vinyl siding
- Windows & doors
- Air vents
- RV, tractor trailers & buses



Provided information obtained from manufacturer's product labels, technical data sheets and SDS.

\* Titebond WeatherMaster ULTIMATE MP Translucent (#71111) is NOT paintable.

† ChemLink and Duralink are trademarks of Chem Link; Dow Corning is a registered trademark of Dow Corning Corporation; MasterSeal is a registered trademark and NP1 is a trademark of BASF; RainBuster is a registered trademark of Top Industrial, Inc.; Sikaflex is a registered trademark of Sika; Dymonic and Vulkem are registered trademarks of Tremco, Inc.

‡ Maximum temperature over 200°F is for short term exposures.

VISIT [WWW.TITEBOND.COM](http://WWW.TITEBOND.COM) FOR THE  
MOST UP-TO-DATE PRODUCT INFORMATION



**Franklin International**

Columbus, Ohio 43207

614.443.0241

(Technical Service 1.800.347.4583)

© 2017 BCM2792 11/17 FF1101

	WeatherMaster™ Ultimate MP	Bostik 915	Chem Link™ DuraLink™ 50†	Dow Corning® 795†	MasterSeal® NPI™†	RainBuster® 850†	RainBuster® 975†	Sikaflex® 1a†	Tremco Dymonic® FC†	Vulkem® 116†
PAINTABLE	Yes, 2 Hours (Except Translucent)	Yes, with latex-based paints once fully cured. Pretest to ensure compatibility.	Within 24 hours. Test and evaluate all paints before application.	No	Yes, Compatibility Test Required	Yes, for Best Results, Paint after 72 Hours	Yes, for Best Results, Paint after 72 Hours	Yes, Compatibility Test Required	Yes, Not Stated	Yes, Not Stated
% SOLIDS	99%	96%	100%	Not Stated	100%	96-99%	96-99%	Not Stated	100%	94%
SHRINKAGE	1%	Not Stated	0%	Not Stated	0%	0%	0%	Not Stated	Not Stated	6%
JOINT FLEXIBILT Y	50%	35%	50%	50%	35%	35%	35%	35%	35%	25%
VOC-COMPLIANT	19.8 g/L	33.6 - 39.2 g/L	Less than19 g/L	28 g/L	35 g/L	VOC-Compliant under AQMD & CARB	9 g/L	40 g/L	6 g/L	47 g/L
GAP FILLING (WIDTH)	Unlimited Width. Max Depth of 1/2"	1/2"	1/2"	Not Stated	1/2"	1"	1"	1/2"	1/2"	1/2"
COLD WEATHER EXTRUSION	0°F	Above 40°F	32°F	Not Stated	Only if substrates are completely dry, clean and free of moisture. Store at room temperature for 24 hours before using.	20°F. If below 40°F, condition product at 70°F prior to using for best results.	20°F. If below 40°F, condition product at 70°F prior to using for best results.	40°F. For cold weather application, condition units at approximately 70°F; remove prior to using.	Above 40°F	Above 40°F
FOAM BOARD	Yes	Yes	Yes	Not Stated	Not Stated	Not Stated	Yes	Not Stated	Not Stated	Not Stated
ODOR/VAPOR	Very Mild	Solvent	Mild	Slight	Mild	Mild	Mild	Odorless/Aromatic	Mild	Mild
OCCUPIED STRUCTURES	Yes	Use with Adequate Ventilation or Wear Mask	Yes	Yes; Only in a Well-Ventilated Area	Ensure Adequate Ventilation	Yes; Only in a Well-Ventilated Area	Not Stated	Yes, Use Only with Adequate Ventilation	Yes, Use Only with Adequate Ventilation	No
SERVICE TEMPERATURE	-75° to 300°F‡	-40° to 150°F	-40° to 200°F	-40° to 300°F	-40° to 180°F	Not Stated	-75° to 300°F (For Short Periods)	-40° to 170°F	Not Stated	Not Stated
CARTRIDGE	Plastic (10.1 oz. Removable Nozzle) & 20 oz. Sausage Pack	Fiber (10.1 oz.), 20 oz. Sausages, 5 Gallon Pails & 52 Gallon Drums	Plastic (10.1 oz.), 20 oz. Sausages, 2 and 5 Gallon Pails or 50 Gallon Drums by Special Order	Plastic (10.3 oz.), 20 oz. Sausages, 2 Gallon & 4.5 Gallon Bulk Containers	Fiber (10.1 oz. Fixed Nozzle) & 20 oz. ProPaks	Fiber (10.1 oz. Fixed Nozzle) & 20 oz. Sausage Tubes	Plastic (10.1 oz. Fixed Nozzle)	Fiber (10.1 oz. Fixed Nozzle), 20 oz. Uni-Pac Sausages, 5 Gallon Pail & 55 Gallon Drum	Fiber (10.1 oz Fixed Nozzle) & 20 oz. Sausages	Fiber (10.1 oz. Fixed Nozzle), 20 oz. Sausages, 2 Gallon Pails, 5 Gallon Pails & 55 Gallon Drums
WARRANTY	Limited	Limited	Limited	Limited	Limited	Lifetime	Lifetime	1 Year	Tremco warrants its products to be free of defects in materials, but makes no warranty as to appearance or color. Replace or refund.	Tremco warrants its products to be free of defects in materials, but makes no warranty as to appearance or color. Replace or refund.
STANDARD COLORS	20+ Colors	10 Colors	13 Colors & Clear	16 Colors	12 Colors	6 Colors	7 Colors	9 Colors	18 Colors	16 Colors
CLASS	Class 50	Class 35	Class 50	Class 50	Class 35	Class 35	Class 35	Class 35	Class 35	Class 25
MANUFACTURED	Owned & Made in the USA	Not Stated	Not Stated	Not Stated	Not Stated	Not Stated	Not Stated	Not Stated	USA & Canada	USA & Canada
SHELF LIFE	24 Months	Not Stated	12 Months, 6 Months for Pails	12 Months	12 Months	12 Months	12 Months	12 Months, 6 Months for Pails & Drums	Not Stated	Not Stated